

BX Specifications		BX2190	BX2390 Deluxe	BX2690 Premium	BX2390S	BX2690S Premium
Engine						
Type		Liquid-Cooled, 4-Cycle Diesel				
Engine Gross HP (kw) at Rated RPM		19.3 (14.4) @ 3200	21.6 (16.1) @ 3200	23.9 (17.8) @ 3600	21.6 (16.1) @ 3200	23.9 (17.8) @ 3600
PTO Power HP (kw) at Rated RPM		15.7 (11.7) @ 3200	17.2 (12.8) @ 3200	18.7 (14.0) @ 3600	17.6 (13.1) @ 3200	18.7 (14.0) @ 3600
Displacement	cc	778	898			
Fuel Tank Capacity	gal (L)	6.6 (25)				
Drivetrain						
Transmission		HST, High-Low Gear Shift				
Drive Method		4WD				
Brakes		Wet Disk				
PTO		Independent PTO with Hydraulic Clutch				
Rear PTO Engine Speed	RPM	540 / 3140	540 / 3140	540 / 3505	540 / 3140	540 / 3505
Mid-PTO Engine Speed	RPM	2629 / 3200	2629 / 3200	2651 / 3600	2629 / 3200	2651 / 3600
Hydraulics						
Pump Output at Rated RPM	gpm (l/min)	6.2 (23.6)	6.8 (25.8)	7.7 (29.0)	6.2 (23.6)	7.7 (29.0)
3-Point Hitch		SAE Category I			Optional	
Lift Capacity at 24 in. Behind Pin	lbs (kg)	950 (431)	892 (405)	898 (407)	950 (431)	898 (407)
Steering		Hydraulic Power Steering				
Tire Size						
Front*		18×8.5-10				
Rear*		26×12-12				
Traveling Speeds at Rated Engine RPM						
Forward	mph (km/h)	0-8.4 (0-13.5)	0-8.4 (0-13.5)	0-8.9 (0-14.3)	0-8.4 (0-13.5)	0-8.9 (0-14.3)
Reverse	mph (km/h)	0-6.5 (0-10.5)	0-6.5 (0-10.5)	0-6.9 (0-11.1)	0-6.5 (0-10.5)	0-6.9 (0-11.1)
Dimensions						
Length with 3-Point Hitch	in (mm)	95.5 (2425)				
Width	in (mm)	44.5 (1130)				
Height with ROPS	in (mm)	83.0 (2111)	82.0 (2198)	86.5 (2083)		
Wheelbase	in (mm)	55.1 (1400)				
Ground clearance	in (mm)	8.4 (213)				
Tread - Front	in (mm)	36.6 (930)				
Tread - Rear	in (mm)	32.3 (820)	34.2 (870)	34.2 (870)	32.3 (820)	34.2 (870)
Turning Radius (w/o brake)	ft (m)	5.9 (1.8)	5.6 (1.7)	5.6 (1.7)	5.9 (1.8)	5.6 (1.7)
Tractor Weight with ROPS	lb (kg)	1433 (650)	1477 (670)		1598 (725)	1620 (735)

* Applicable to R3 turf, R4 industrial and R14 hybrid models.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.