

| Electrified Drive Train                            |             | T4 Electric Power   |
|--|-------------|---|
| Architecture voltage                               | V           | 400   |
| Maximum continuous torque                          | Nm          | 320   |
| Battery capacity                                   | kWh         | 110   |
| Net energy available for use                       | kWh         | 95  |
| Rated power  | hp (kW)     | 74 (55)   |
| PTO power  | hp (kW)     | 65 (48)   |
| Charging System                                    |             |   |
| Plug compatibility                                 |             | CCS (DC fast charging), J1772 (AC std charging) / Tesla compatible with adaptor |
| Charge inlet plug                                  |             | CCS/SAE type 2 (EU) combo AC/DC / type 1 (US)                                   |
| AC max charge rate                                 | (kW)        | Up to 19  |
| DC max charge rate                                 | (kW)        | Up to 120   |
| Entry-level AC charger*                            |             | ○   |
| Standard AC charger*                               |             | ○   |
| Economy fast DC*                                   |             | ○   |
| Exportable Power                                   |             |   |
| Voltage  | V           | 110/220 (US) / 220 (EU)   |
| Max power output                                   | V (kW)      | 110 (1.8) / 220 (5.8)   |
| Current  | V (A)       | 110 (15) / 220 (25)   |
| PTO  |             |   |
| PTO speeds   |             | 540 / 540E  |
| PTO engagement                                     |             | Electrohydraulic  |
| 3-point Hitch                                      |             |   |
| Maximum lift capacity                              | lbs (kg)    | 6085 (2760)   |
| Rear lift capacity at 610mm (24 in) behind balls   | lbs (kg)    | 4564 (2070)   |
| Category   |             | I & II  |
| Draft control                                      |             | Mechanical  |
| Lift-O-Matic™ Plus                                 |             | ●   |
| Hydraulics   |             |   |
| Circuit type                                       |             | Open centre   |
| Implement pump max flow                            | gpm (l/min) | 12.9 (48)   |
| Steering pump flow                                 | gpm (l/min) | 9.5 (36)  |
| Total hydraulic pump flow                          | gpm (l/min) | 22 (84)   |
| Rear remotes                                       |             | 3 + diverter  |
| Front Axle   |             |   |
| Front axle type                                    |             | 4WD   |
| Front axle class                                   |             | 1 HD  |
| Front differential lock                            |             | Limited Slip  |
| Transmission                                       |             |   |
| 12x12 with electronic Powershuttle                 |             | ●   |
| Speed (min - max)                                  | mph kph     | 0.2 (0.3) - 25 (40)   |
| Loader   |             |   |
| Model  |             | 725LU mechanical self-levelling   |
| Max loader height                                  | in (mm)     | 125.9 (3200)  |
| Lift capacity max height @ 800 mm                  | lbs (kg)    | 2645.5 (1200)   |
| Bucket width                                       | in (mm)     | 84 (2134)   |
| Dimensions & Weights                               |             |   |
| Wheelbase  | in (mm)     | 83.9 (2132)   |
| Total length                                       | in (mm)     | 157 (4000)  |
| Total length (with loader & bucket)                | in (mm)     | 212.6 (5400)  |
| Overall height (from ground to cab roof)           | in (mm)     | 110 (2800)  |
| Overall width (min - max)                          | in (mm)     | 82 (2100) - 94.5 (2400)   |
| Ground clearance                                   | in (mm)     | 13.9 (355)  |
| Shipping weight (without loader)                   | lbs (kg)    | 9260 (4200)   |
| Shipping weight (with loader, bucket, & ballast)** | lbs (kg)    | 10802 (4900)  |

● Standard ○ Optional \* Available through CNH Industrial Parts \*\* Design target



Learn more at [www.newholland.com](http://www.newholland.com)

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2023 CNH Industrial America LLC. All rights reserved. New Holland is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies, other than owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

